



## Product Data Sheet

# 5212660322SS

### Industrial castor 125 mm with plate fixing 105x85 mm, black solid rubber tyre

Housing made of zinc-chromatized, pressed steel with double ball race swivel head with plate fixing 105x85 mm, screwed wheel axel.

Wheel with roller bearing with black rubber tyre, RAL 9004. Hub in black PP.

### Technical specification

|                                |                          |
|--------------------------------|--------------------------|
| Wheel diameter (mm)            | 125                      |
| Width of tread (mm)            | 37                       |
| Offset (mm)                    | 32                       |
| Swivel radius (mm)             | 102,5                    |
| Size of plate (mm)             | 105x85                   |
| CC distance (mm)               | 80x60                    |
| Overall height (mm)            | 156                      |
| Dynamic load capacity (kg)     | 100                      |
| Hardness of tread (shore)      | 85° Shore A              |
| Test method standard           | EN 12532                 |
| Temperature area C°            | -20°C to +60°C           |
| Net weight kg                  | 0,94                     |
| Environmental status           | RoHS (EU) - NOT Approved |
| Hole diameter, plate (mm)      | 9x13                     |
| Wheel attachment               | Top plate                |
| Diameter centre bolt hole (mm) | ..                       |
| Castor model (brake)           | ..                       |
| Hole diameter loose wheel (mm) | ..                       |
| Tread width, loose wheel (mm)  | ..                       |
| Wheel bearing                  | Roller bearing           |
| Statistic number               | 8302200090               |

